

## Digital Depth Gage MarCal 30 EWN



Version A



Version B

REFERENCE

### Applications

- Ideal for measuring the width of grooves and distances between grooves

### Features

- |  |   |   |   |
|--|---|---|---|
| <p><b>Functions:</b><br/>ON/OFF<br/>RESET (Set display to zero)<br/>mm/inch<br/>PRESET (enter a numerical value)<br/>Reference-Lock/Unlock<br/>DATA (Data transmission via connection cable)<br/>Auto-ON/OFF</p> | <ul style="list-style-type: none"> <li>• Immediate measurement due to the Reference system</li> <li>• Excellent resistance against dust, coolants and lubricants, protection class IP67</li> <li>• MarConnect data output, choose alternatively: USB, OPTO RS232C or Digimatic</li> </ul> | <ul style="list-style-type: none"> <li>• Dirt wipers are integrated in the slide</li> <li>• Life of the battery up to 3 years</li> <li>• Max measuring speed 2.5 m/s (100"/s)</li> <li>• High contrast LCD with 8.5 mm high digits</li> <li>• Beam and cross beam are made of hardened stainless steel</li> </ul> | <ul style="list-style-type: none"> <li>• Locking screw</li> <li>• Supplied with: Case, battery, operating instructions. Version A: Anvils 30 ENT (1 mm), 902 and 903</li> </ul> |
|--|---|---|---|

### Technical Data

Measuring range		Length of cross beam	Resolution	Error limit G	Version	Order no.
mm	(inch)	mm	mm / inch	mm		
100	(4")	85	0.01 / .0005"	0.03	A	<b>4126512</b>
200	(8")	100	0.01 / .0005"	0.03	B	<b>4126517</b>
300	(12")	150	0.01 / .0005"	0.03	B	<b>4126518</b>